

SAFETY DATA SHEET

sds Inv.# 1019

1. Product and Company Identification

Product number 58120
Material name 14.5 OZ WHITE SHOW FOAM
Revision date 11-19-2013
Company information Stone Manufacturing & Supply Company, Inc.
1212 Kansas Ave
Kansas City, MO 64127 United States
Ph. 1-816-231-4020 (for information only)
(SMFG)
Emergency telephone US 1-800-424-9300
Emergency telephone outside US 1-703-527-3887
Version # 02
Supersedes date 12-11-2009
Mfg id code 1000002939

2. Hazards Identification

Emergency overview DANGER
CONTENTS UNDER PRESSURE.
Aerosol. Pressurized container may explode when exposed to heat or flame. May cause flash fire or explosion.

Will be easily ignited by heat, spark or flames. Cancer hazard. Prolonged exposure may cause chronic effects. Flammable.

OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects
Routes of exposure Inhalation.
Eyes Contact with eyes may cause irritation.
Skin May be harmful if absorbed through skin.
Inhalation May cause cancer by inhalation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.
Ingestion Exposure by ingestion of an aerosol is unlikely.
Target organs Central nervous system.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Chronic effects May be harmful if absorbed through skin. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage.
Signs and symptoms Narcosis. Decrease in motor functions. Behavioral changes.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Butane	106-97-8	2.5 - 10
Propane	74-98-6	2.5 - 10
Triethanolamine	102-71-6	2.5 - 10
Other components below reportable levels		90 - 100

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms occur.
Skin contact	Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if symptoms occur. For minor skin contact, avoid spreading material on unaffected skin.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms occur.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

5. Fire Fighting Measures

Flammable properties Flammable by OSHA criteria. Heat may cause the containers to explode. Vapors may travel considerable distance to a source of ignition and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media Water.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental Release Measures

Personal precautions Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.

Environmental precautions Do not contaminate water.

Methods for containment Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Prevent entry into waterways, sewer, basements or confined areas.

Methods for cleaning up Should not be released into the environment. Stop the flow of material, if this is without risk. Isolate area until gas has dispersed. Following product recovery, flush area with water. For waste disposal, see section 13 of the MSDS.

7. Handling and Storage

Handling

Vapors may form explosive mixtures with air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get this material in contact with skin. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes. Avoid prolonged exposure. Use only in area provided with appropriate exhaust ventilation.

Storage

Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the MSDS). Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

Personal protective equipment

Eye / face protection Chemical goggles are recommended.

Skin protection Wear protective gloves.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

General hygiene considerations When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance	Not available.
Auto-ignition temperature	669.72 °F (354.29 °C) estimated
Boiling point	195.8 °F (91 °C) estimated
Color	Not available.
Flammability limits in air, upper, % by volume	8.5 % estimated
Flammability limits in air, lower, % by volume	2.1 % estimated
Flash point	-156.00 °F (-104.44 °C) Propellant estimated
Form	Aerosol.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Physical state	Gas.
Solubility (water)	Not available.
Specific gravity	0.917 estimated
Vapor pressure	65 psig @68F estimated

Other data

Heat of combustion 3.7 kJ/g estimated

10. Chemical Stability & Reactivity Information**Chemical stability** Risk of ignition.**Conditions to avoid** Heat, flames and sparks. Avoid temperatures exceeding the flash point.**Hazardous decomposition products** No hazardous decomposition products are known.**Possibility of hazardous reactions** Hazardous polymerization does not occur.**11. Toxicological Information****Toxicological data**

Product	Species	Test Results
14.5 OZ WHITE SHOW FOAM (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rat	67809.7969 mg/kg, estimated
<i>Inhalation</i>		
LC50	Mouse	18323.4082 mg/l, 2 Hours, estimated
	Rat	55948.1563 mg/l, 15 Minutes, estimated
		17730.5918 mg/l, 4 Hours, estimated
		10461.0488 mg/l/4h, estimated
<i>Oral</i>		
LD50	Dog	405.9829 g/kg, estimated
	Guinea pig	393.1624 g/kg, estimated
	Mouse	463.7877 g/kg, estimated
	Rabbit	384.6154 g/kg, estimated
	Rat	146.3451 g/kg, estimated
<i>Other</i>		
LD50	Mouse	26162.3516 mg/kg, estimated
	Rat	97810.8516 mg/kg, estimated
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
		658 mg/l/4h
Triethanolamine (CAS 102-71-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 20000 mg/kg
<i>Oral</i>		
LD50	Guinea pig	5300 mg/kg
	Rat	8 g/kg

Components	Species	Test Results
<i>Other</i>		
LD50	Mouse	1450 mg/kg

* Estimates for product may be based on additional component data not shown.

Chronic effects Hazardous by OSHA criteria. May be harmful if absorbed through skin. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Carcinogenicity Hazardous by OSHA criteria.

IARC Monographs. Overall Evaluation of Carcinogenicity

Triethanolamine (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

Neurological effects Hazardous by OSHA criteria.

Further information Symptoms may be delayed.

12. Ecological Information

Ecotoxicological data

Product	Species	Test Results
14.5 OZ WHITE SHOW FOAM (CAS Mixture)		
Algae	IC50	Algae 7089.3374 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia 15013.4414 mg/l, 48 hours, estimated

Components	Species	Test Results
Triethanolamine (CAS 102-71-6)		
Algae	IC50	Algae 216 mg/L, 72 Hours
Aquatic		
Crustacea	EC50	Water flea (Ceriodaphnia dubia) 565.2 - 658.3 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 10610 - 13010 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Ecotoxicity Contains a substance which causes risk of hazardous effects to the environment.

Environmental effects An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Persistence and degradability Not available.

Bioaccumulation / Accumulation

Bioaccumulative potential

Octanol/water partition coefficient log Kow

Butane	2.89
Propane	2.36
Triethanolamine	-1

Partition coefficient

Butane	2.89
Propane	2.36
Triethanolamine	-1

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Disposal instructions Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

DOT

Basic shipping requirements:

UN number	UN1950
Proper shipping name	Aerosols, flammable
Hazard class	2.1
Special precautions	Read safety instructions, MSDS and emergency procedures before handling.
Additional information:	
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Labels required	2.1
ERG code	10L
Special precautions for user	Read safety instructions, MSDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Labels required	None
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
Packaging Exceptions	LTD QTY

DOT



IATA; IMDG



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Not listed.

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Not regulated.

DEA Exempt Chemical Mixtures Code Number

Not regulated.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

Section 302 extremely hazardous substance No

SARA 311/312 Hazardous chemical No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - New Jersey RTK - Substances: Listed substance

Butane (CAS 106-97-8) Listed.
Propane (CAS 74-98-6) Listed.
Triethanolamine (CAS 102-71-6) Listed.

US. Pennsylvania RTK - Hazardous Substances

Butane (CAS 106-97-8) Listed.
Propane (CAS 74-98-6) Listed.
Triethanolamine (CAS 102-71-6) Listed.

16. Other Information

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This data sheet contains changes from the previous version in section(s):

Product and Company Identification: Product Review
Composition / Information on Ingredients: Disclosure Overrides
Regulatory Information: Canada